

# ROLL MASTIC™ 115

## DUCT SEALANT FOIL TAPE WITH BUTYL RUBBER ADHESIVE



### FEATURES

- *UL 181 B-FX Listed*
- *Use indoors and outdoors*
- *Repositionable for easier application*
- *Excellent adhesion/seals on contact*
- *Excellent resistance to cold, heat, water, and sunlight*

TECHNICAL SPECIFICATIONS	
Packaging	24 - 72mm x 31mm 16 - 48mm x 31mm
Shelf Life	36 months in unopened boxes
Pressure Rating	Maximum 10" water column pressure
Solids Content	100%
Backing	2 mil. printed foil
Adhesive	Butyl rubber adhesive
Tensile Strength	23 lbs. per inch of width
Color	Aluminum backing with gray adhesive
Temperature Limits	Storage and application... 60°F to 80°F Service..... -40°F to 200°F
Class 1 Smoke and Flame Rating	UNDERWRITERS LABORATORIES INC. GENERAL USE TAPE Applied to organic, Reinforced Cement Board. Flame Spread .....5 Smoke Developed .....0 82P4 Tested in accordance with UL 723, and ASTM E-84. Satisfies the requirements of NFPA 90A, 90B, and 225.

### DESCRIPTION

**ROLL MASTIC 115** is a UL 181 B-FX Listed pressure sensitive tape with a 2 mils. printed foil backing, and 15 mils. of butyl rubber adhesive with a plastic release liner. It is formulated to be repositionable for easier application. Meets all code requirements for sealing HVAC duct systems.

### RECOMMENDED USES

Use **ROLL MASTIC 115** as a sealant to seal all types of HVAC duct systems including metal (galvanized, aluminum, stainless), fiberglass duct board, and flexible duct. Use anywhere a weather-proof, or airtight seal is required. Has excellent adhesion to metal, wood, concrete, and most construction related materials.

### APPLICATION INSTRUCTIONS

Prior to application remove all dirt, oils, grease, and foreign matter that might interfere with adhesion from the surface. Cut to desired length. Remove the plastic release liner. Apply to surface. Apply pressure to tape surface to insure good adhesion. Smooth out any wrinkles to allow for maximum surface contact.

### LIMITED WARRANTY

Polymer Adhesives Sealant Systems, Inc. (PASS) makes the limited Expressed Warranty that at the time of delivery the product shall be free from defects in materials and workmanship. The Limited Expressed Warranty is in lieu of any other expressed or implied warranties of merchantability or fitness. The sole remedy for breach of this Limited Expressed Warranty shall be the refund of the purchase price or replacement of material at the discretion of PASS. All other liability is negated and disclaimed and PASS shall not be liable for any incidental consequential damages.

Polymer Adhesives Sealant Systems Inc., is proud to be affiliated with the following organizations:



LISTED  
UL 181B-FX  
82P4



**POLYMER ADHESIVES**

**SEALANT SYSTEMS, INC.**

[www.polymeradhesives.com](http://www.polymeradhesives.com)