



### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : AIR SEAL ZERO

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : High Performance Duct Sealant

#### 1.3. Details of the supplier of the safety data sheet

Polymer Adhesives  
501 Garrett Morris Pkwy  
Mineral Wells, TX 76067 - USA  
T 1 (888) 721-7325

#### 1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable liquids, Category 2 H225  
Serious eye damage/eye irritation, Category 2A H319  
Sensitisation — Skin, Category 1 H317

Full text of H statements: see section 16

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation

Precautionary statements (GHS-US) : P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/Bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing fume, mist, spray, vapors  
P264 - Wash hands thoroughly after handling  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear eye protection, protective gloves, protective clothing  
P302+P352 - If on skin: Wash with plenty of water  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P363 - Wash contaminated clothing before reuse  
P403+P235 - Store in a well-ventilated place. Keep cool  
P501 - Dispose of contents/container to comply with applicable local, national and international regulation

#### 2.3. Other hazards

This product contains greater than 0.1% by weight titanium dioxide. Titanium dioxide inhalation studies in rats indicate that there is sufficient evidence that inhalation of excessive amounts of titanium dioxide is carcinogenic in the lungs of experimental animals. Titanium dioxide is classified as "Group 2B (possibly carcinogenic to humans)" by IARC. Titanium dioxide is in a form that is not available for respiration.

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

# AirSeal Zero

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
tert-Butyl acetate	(CAS No) 540-88-5	16 - 18	Flam. Liq. 2, H225
Acetone	(CAS No) 67-64-1	9 - 16	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Titanium dioxide	(CAS No) 13463-67-7	0.5 - 1	Carc. 2, H351
2-Benzotriazolyl-4-methylphenol	(CAS No) 2440-22-4	0 - 0.4	Skin Sens. 1, H317

Full text of hazard classes and H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : May cause an allergic skin reaction.
- Symptoms/injuries after eye contact : Causes serious eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor. Combustion products: Carbon monoxide. Carbon dioxide. May release flammable gases.
- Explosion hazard : May form flammable/explosive vapor-air mixture. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.
- Reactivity : None known under normal conditions of use.

#### 5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Prevent firefighting water from entering the environment.
- Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

# AirSeal Zero

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For disposal of residues refer to section 13: Disposal considerations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling	: Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Avoid breathing fume, mist, spray, vapors.
Hygiene measures	: Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting, and ventilating equipment.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from incompatible materials. Keep in fireproof place. Keep container tightly closed.
Incompatible materials	: Strong oxidizers. Strong acids, bases.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Acetone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
IDLH	US IDLH (ppm)	2500 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
tert-Butyl acetate (540-88-5)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
IDLH	US IDLH (ppm)	1500 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	950 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
2-Benzotriazolyl-4-methylphenol (2440-22-4)		
Not applicable		
Titanium dioxide (13463-67-7)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
ACGIH	Remark (ACGIH)	LRT irr; A3
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>

### 8.2. Exposure controls

Appropriate engineering controls	: Provide local exhaust or general room ventilation to minimize vapor concentrations. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Wear impervious gloves e.g. PVC, nitrile rubber, butyl rubber.
Eye protection	: Chemical goggles or safety glasses.
Skin and body protection	: Long sleeved protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection.

# AirSeal Zero

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Other information : Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Paste
Appearance	: Viscous mastic
Color	: Gray
Odor	: Sweet, pungent, camphor-like, ketone
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 55 °C (132 °F)
Flash point	: -20 °C (-4 °F)
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: 7.7 (Butyl Acetate = 1)
Flammability (solid, gas)	: Not applicable
Vapor pressure	: 185 mmHg
Relative vapor density at 20 °C	: No data available
Relative density	: 1.25 +/- 0.05 g/cc
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 325,000 - 600,000 cps at 75 °F
Viscosity, dynamic	: No data available
Explosive limits	: Lower explosive limit (LEL): 1.26 vol % Upper explosive limit (UEL): 12.8 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available

#### 9.2. Other information

California VOC Content for districts that do not exempt Tertiary Butyl Acetate (Calculated Values)

VOC less water, less exempt compounds: <260g/l

% VOC: <26 %

EPA VOC Content (Calculated Values)

VOC less water, less exempt compounds: 0 g/l

% VOC: 0 %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

None known under normal conditions of use.

#### 10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization is unlikely to occur.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Heat sources.

#### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

#### 10.6. Hazardous decomposition products

None known. Combustion products: Carbon monoxide. Carbon dioxide. May release flammable gases.

# AirSeal Zero

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Likely routes of exposure : Ingestion; Inhalation; Skin and Eye contact  
 Acute toxicity : Not classified

<b>Acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg
LC50 inhalation rat (mg/l)	50100 mg/m <sup>3</sup> (Exposure time: 8 h)

<b>tert-Butyl acetate (540-88-5)</b>	
LD50 oral rat	4100 mg/kg
LC50 inhalation rat (mg/l)	> 2230 mg/m <sup>3</sup> (Exposure time: 4 h)

Skin corrosion/irritation : Not classified  
 Serious eye damage/irritation : Causes serious eye irritation.  
 Respiratory or skin sensitisation : May cause an allergic skin reaction.  
 Germ cell mutagenicity : Not classified  
 Carcinogenicity : Not classified (This product contains greater than 0.1% by weight titanium dioxide. Titanium dioxide inhalation studies in rats indicate that there is sufficient evidence that inhalation of excessive amounts of titanium dioxide is carcinogenic in the lungs of experimental animals. Titanium dioxide is classified as "Group 2B (possibly carcinogenic to humans)" by IARC. Titanium dioxide is in a form that is not available for respiration.)

<b>Titanium dioxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified  
 Specific target organ toxicity (single exposure) : Not classified  
 Specific target organ toxicity (repeated exposure) : Not classified  
 Aspiration hazard : Not classified  
 Symptoms/injuries after skin contact : May cause an allergic skin reaction.  
 Symptoms/injuries after eye contact : Causes serious eye irritation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

<b>Acetone (67-64-1)</b>	
LC50 fish 1	4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)

<b>tert-Butyl acetate (540-88-5)</b>	
LC50 fish 1	296 - 362 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

#### 12.2. Persistence and degradability

<b>AIR SEAL ZERO</b>	
Persistence and degradability	Not established.

#### 12.3. Bioaccumulative potential

<b>AIR SEAL ZERO</b>	
Bioaccumulative potential	Not established.

<b>Acetone (67-64-1)</b>	
BCF fish 1	0.69
Log Pow	-0.24

<b>tert-Butyl acetate (540-88-5)</b>	
Log Pow	1.38

# AirSeal Zero

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.  
GWPmix comment : No known effects from this product.  
Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container to comply with applicable local, national and international regulation.  
Additional information : Handle empty containers with care because residual vapors are flammable.  
Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1133 Adhesives, containing flammable liquids (Acetone , tert-Butyl acetate mixture), 3, II  
UN-No.(DOT) : UN1133  
Proper Shipping Name (DOT) : ADHESIVES, containing flammable liquids (Acetone ; tert-Butyl acetate mixture)  
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Packing group (DOT) : II - Medium Danger  
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173  
DOT Packaging Bulk (49 CFR 173.xxx) : 242  
DOT Symbols : G - Identifies PSN requiring a technical name  
DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in §173.150(b)(2) of this subchapter for inner packagings may be increased to 5 L (1.3 gallons).  
383 - For transportation by motor vehicle, substances meeting the conditions for high viscosity flammable liquids as prescribed in Sec. 173.121(b)(1)(i), (b)(1)(ii), and (b)(1)(iv) of this subchapter, may be reassigned to Packing Group III under the following conditions: a. Packaging must be UN standard metal drums attached with heavy duty steel strapping to a pallet; and b. The capacity of each drum must not exceed 220 L (58 gallons)  
B52 - Notwithstanding the provisions of §173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized  
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling  
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F)  
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP  
DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

# AirSeal Zero

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

### TDG

Transport document description	: UN1133 ADHESIVES, containing flammable liquids (Acetone, tert-Butyl acetate mixture), 3, II
UN-No. (TDG)	: UN1133
Proper Shipping Name (TDG)	: ADHESIVES, containing flammable liquids (Acetone, tert-Butyl acetate mixture)
TDG Primary Hazard Classes	: 3 - Class 3 - Flammable Liquids
Packing group	: II - Medium Danger
TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a)UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; (b)UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; (c)UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; (d)UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e)UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act". (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a)UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b)UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS. SOR/2014-306,150 - An emergency response assistance plan (ERAP) is required for these dangerous goods under subsection 7.1(6) of Part 7 (Emergency Response Assistance Plan)
Explosive Limit and Limited Quantity Index	: 1 L
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5 L

### Transport by sea

UN-No. (IMDG)	: 1133
Proper Shipping Name (IMDG)	: ADHESIVE containing flammable liquids (ACETONE , TERT-BUTYL ACETATE MIXTURE)
Class (IMDG)	: 3 - ADHESIVE
Packing group (IMDG)	: II - substances presenting medium danger
Limited quantities (IMDG)	: 1 L

### Air transport

UN-No. (IATA)	: 1133
Proper Shipping Name (IATA)	: ADHESIVE containing flammable liquids. (Acetone , tert-Butyl acetate mixture)
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

#### CANADA

# AirSeal Zero

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

<b>Acetone (67-64-1)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
<b>tert-Butyl acetate (540-88-5)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid
<b>2-Benzotriazolyl-4-methylphenol (2440-22-4)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

### EU-Regulations

<b>Acetone (67-64-1)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
<b>tert-Butyl acetate (540-88-5)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
<b>2-Benzotriazolyl-4-methylphenol (2440-22-4)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

### National regulations

<b>Acetone (67-64-1)</b>	
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the Canadian IDL (Ingredient Disclosure List) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on CICR (Turkish Inventory and Control of Chemicals)	
<b>tert-Butyl acetate (540-88-5)</b>	
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the Canadian IDL (Ingredient Disclosure List) Listed on INSQ (Mexican National Inventory of Chemical Substances)	
<b>2-Benzotriazolyl-4-methylphenol (2440-22-4)</b>	
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on the Korean ECL (Existing Chemicals List) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on CICR (Turkish Inventory and Control of Chemicals)	

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

Date of Preparation : May 12, 2016  
Other information : None.

Full text of H-statements:

H225	Highly flammable liquid and vapor
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Abbreviations and acronyms:



# AirSeal Zero

## Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

ACGIH	American Conference of Government Industrial Hygienists
IARC	International Agency for Research on Cancer
IDLH	Immediately Dangerous to Life or Health
IRR	Irritation
NIOSH	National Institute for Occupational Safety and Health
PEL	Permissible Exposure Level
PVC	Polyvinyl chloride
Sens.	Skin sensitization
STEL	Short-Term Exposure Limit

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*